Rodagon-G

For extreme enlargements the most important thing is focus

Rodenstock can offer different enlarging lens types for different applications and quality demands: The current range begins with the favorably priced three-element Rogonar lens, moves on to include the high-quality fourelement Rogonar-S and ends with the top, six-element lenses Rodagon, Rodagon-WA (with enlarged image angle) and the apochromatic Apo-Rodagon-N with six or seven lens elements depending on the focal length. One particularly special product in the range is the Rodagon-G described here. This special lens for picture sizes from the poster format to multi-strip giant enlargements has six elements and has been optimized for the very high enlarging scales. The Rodagon-G comes in focal lengths from 50 mm to 480 mm for film sizes from 35 mm to sheet film 10x12"/24x30 cm and is primarily used in horizontal enlargers.

Note: Separate product information leaflets are available for the enlarging lenses Rodagon, Rodagon-WA and Apo-Rodagon-N which give detailed information on the special features of these lens types together with all technical data.

Conventional film sizes for horizontal enlargers									
Size / Film designation	Format size*	Diagonal*							
Full frame "135"	24×36 mm	43.3 mm							
4.5×6 cm / Roll film "120" and "220"	42×56 mm	70.0 mm							
6×6 cm / Roll film "120" and "220"	56×56 mm	79.2 mm							
6×7 cm / Roll film "120" and "220"	56×68 mm	88.1 mm							
6×9 cm / Roll film "120" and "220"	56×81 mm	98.5 mm							
9×12 cm / Sheet film	83×114 mm	141.0 mm							
4×5" / Sheet film	96×120 mm	153.7 mm							
13×18 cm / Sheet film	122×171 mm	210.1 mm							
5×7" / Sheet film	121×170 mm	208.7 mm							
18×24 cm / Sheet film	171×231 mm	287.4 mm							
8×10" / Sheet film	194×245 mm	312.5 mm							
24×30 cm / Sheet film	230×290 mm	370.0 mm							
10×12" / Sheet film	245×295 mm	383.5 mm							

^{*} The masks of the printers and their diagonals are slightly smaller.

Technical Data

Nominal focal length	Maxi- mum aperture	max. recommended film size	recommended scale (optimal)	Optimum reproduction scale	Mount-siz	lowest ap	pre-selec	click-stop	illuminate
Rodagon-	G								
50 mm f/2.8 35 mm film-forma		35 mm film-format	15× 50×	25×	0	16	•	•	•
105 mm f/5.6 6×9 cm		10× 40×	20×	1	45	=	-	•	

stop display

on aperture

Rodagon-	G								
50 mm	f/2.8	35 mm film-format	15× 50×	25×	0	16	•	•	•
105 mm	f/5.6	6×9 cm	10× 40×	20×	1	45	=	-	•
150 mm	f/5.6	9×12 cm / 4×5"	10× 40×	20×	1	45	-	-	•
210 mm	f/5.6	13×18 cm / 5×7"	8× 30×	20×	2	45	-/		•
240 mm	f/5.6	13×18 cm / 5×7"	8× 30×	20×	3	45	_		•
300 mm	f/5.6	18×24 cm / 8×10"	8× 30×	20×	3	45	1	-	•
360 mm	f/6.8	18×24 cm / 8×10"	8× 30×	20×	3	45	-	-	•
480 mm	f/8.4	24×30 cm / 10×12"	8× 30×	20×	3	64	-	-	•

Top performance thanks to the optimization of the image reproduction quality for scales of around 20x

As the size of the enlargement increases, the performance limits of the enlarging lens become increasingly visible. In particular, very high demands are made on the resolution and the contrast in finely structured details. The maximum height of conventional enlargers alone means that standard enlarging lenses are designed for scale ranges restricted to around 10x (sheet film) or 20x (35 mm). This is the reason why Rodenstock developed the Rodagon-G, optimized for scales of around 20x to 25x with a recommended scale range depending on the film size and focal length of up to 50x.

The scale range of the Rodagon-G was chosen to link up with the other Rodagon types without any gap: The lower limit given in the above table shows the scale from which the Rodagon-G will show its superior quality to high-quality enlarging lenses with conventional scales. This superiority is visible primarily in the focus and the even better correction of distortion.

In addition, the Rodagon-G features very high uniformity of performance in its recommended scale range over the whole negative area from the center to

Mechanical and optical Data

412.0 mm

146.8 mm

M 112×1.5

filter thread [mm]	flange focal length at ∞	overall length	maximum lens dia. Ø	screw thread [mm]	contact area to rear edge	Effective focal length ± 0.5 %	Principle Point distance HH	Entrance pupil Ø (EnP)	Exit pupil Ø (ExP)	EnP-ExP ratio	Front vertex to EnP	ExP to back vertex
a	b	С	d	е	g						h	i
M 40.5×0.5	47.0 mm	45.0 mm	50.0 mm *	M 39×1/26"	14.0 mm	52.1 mm	- 9.72 mm	17.7 mm	20.8 mm	0.85	19.2 mm	27.3 mm
M 40.5×0.5	100.3 mm	38.0 mm	60.0 mm	M 50×0.75	14.3 mm	104.3 mm	- 2.49 mm	18.0 mm	18.0 mm	1.00	17.6 mm	17.5 mm
M 49×0.75	141.8 mm	50.6 mm	60.0 mm	M 50×0.75	20.5 mm	146.8 mm	- 3.50 mm	25.3 mm	25.3 mm	1.00	24.8 mm	24.5 mm
M ~ 0.75	179.5 mm	65.9 mm	74.5 mm	M 72×1	8.5 mm	207.2 mm	- 4.93 mm	35.7 mm	35.7 mm	1.00	35.0 mm	34.6 mm
M ,, 0.75	230.6 mm	76.9 mm	80.0 mm	M 72×1	32.2 mm	240.2 mm	- 5.71 mm	41.4 mm	41.4 mm	1.00	40.5 mm	40.1 mm
M 86×1	253.3 mm	93.5 mm	93.5 mm	M 90×1	11.5 mm	292.2 mm	- 6.96 mm	50.0 mm	50.0 mm	1.00	49.4 mm	48.8 mm
M 105×1	304.2 mm	116.5 mm	110.0 mm	M 90×1	12.2 mm	347.6 mm	- 4.77 mm	50.5 mm	49.4 mm	1.02	72.4 mm	46.8 mm

17.7 mm

467.4 mm

- 7.65 mm

55.6 mm

M 110×1

the furthermost corners. The contrast is already very high at maximum aperture in the area around the picture center used for focusing so that the focusing process is fast and exact. This is particularly important for very large scales as these make focusing much more difficult due to the lower projection illumination. The optimum working aperture

115.0 mm

is reached by stopping down by only 2 f/numbers. This means that even at the largest scales the exposure times are still so short that the Schwarzschild effect is not a problem.

54.8 mm


1.02

87.7 mm


64.4 mm

Another strength is the very favorable course of light fall-off towards the edge of the picture. This is only

Lens sections at a scale of 1:1



6 elements/4 groups Mount-size 0



Rodagon-G 210 mm f/5.6 6 elements/4 groups Mount-size 2

^{*} Switch lever for half-stop clicks and infinite setting protrudes 2 mm over the mount with a diameter of 50 mm.

possible because the effective image angle of the Rodagon-G is larger than required for the maximum format. This means that the light fall-off is lower than usual even at the largest reproduction scales – when the image angle is utilized the most at a given film size. This is also an important plus because of the Schwarzschild effect (color shift at the edges) resulting from the lower illumination at such large reproduction scales.

The quality of the mount mechanics is just as good as that of the optics. For greater comfort the 50 mm lens has a presetting ring and a diaphragm adjustment that can be switched between click-stops at half numbers and infinite adjustment. All Rodagon-G lenses have an aperture display lit by the light of the enlarger head.

Modulation transfer function (MTF) as a demonstration of quality

The high imaging quality of Rodenstock Rodagon-G lenses is documented in the MTF curves and diagrams for relative light drop-off, distortion and longitudinal chromatic aberration on the following data sheet pages.

The MTF curves show the contrast of fine grating structures in dependence on the image height (0 = center, maximal value = image circle circumference). The "sagittal" curves apply to structures extending radially from the image circle center and the dotted "meridional" curves to structures running tangentially or in circular form around the image circle center. The topmost curve pair applies to the lowest spatial frequency (lp/mm = line pairs per millimeter), the bottommost to the highest. The film format-dependent spatial frequencies are given over the MTF diagram (e.g. for 35 mm 5 lp/mm to 40 lp/mm).

The top diagram applies to the open diaphragm, the bottom for the recommended working aperture


(stopped down two numbers). The higher the curves are and the less they fall off towards the edge, the better it is. While diffraction sets physical limits to the imaging quality, the Rodagon-G comes incredibly close to these limits.


The diagram with the relative light drop-off shows how uniformly the image field is illuminated. With an open diaphragm, the edge brightness due to mount vignetting falls somewhat; stopping down by one number eliminates vignetting almost completely, and stopping down by two numbers will put the brightness right at the physical limit (curve "1-cos4").

Distortion varies with the imaging scale. With the Rodagon-G it is optimized for the much larger scales of the horizontal enlarger when compared to conventional enlarging lenses so that even in the most unfavorable case it remains so low that it can be neglected to all practical intent in imagewise photography. Because the distortion of Rodagon-G enlarging lenses is contrary to that of the Rodenstock Apo-Sironar taking lenses for roll and sheet film due to the "reversed" ray path, shots taken with these taking lenses give the ideal case of enlargement with practically no distortion whatsoever.

The longitudinal chromatic deviation shows the different position of the focal point for different wavelengths (colors). When enlarging black-and-white prints, only the left third of the diagram is of relevance because b/w papers are only sensitive to green and possibly slightly to green; for color enlargers the whole area is important. In this regard, too, the Rodagon-G lenses are at the same level as the best taking lenses.


Rodagon-G 50 mm f/2.8







Named frequencies [line pairs/mm] in modular transfer function (MTF) as well as diagrams of relative light fall-off, distortion and longitudinal color aberration refer to film plane.


meridional, O Diffraction limited value










Rodagon-G 105 mm f/5.6










meridional, O Diffraction limited value












Rodagon-G 150 mm f/5.6








____ sagittal, × Diffraction limited value meridional, © Diffraction limited value

Named frequencies [line pairs/mm] in modular transfer function (MTF) as well as diagrams of relative light fall-off, distortion and longitudinal color aberration refer to film plane.













Rodagon-G 210 mm f/5.6









meridional, @ Diffraction limited value









Longitudinal color aberration


Rodagon-G 240 mm f/5.6







_____ sagittal, × Diffraction limited value

Named frequencies [line pairs/mm] in modular transfer function (MTF) as well as diagrams of relative light fall-off, distortion and longitudinal color aberration refer to film plane.









Longitudinal color aberration


Rodagon-G 360 mm f/6.8







____ sagittal, × Diffraction limited value meridional, O Diffraction limited value

Named frequencies [line pairs/mm] in modular transfer function (MTF) as well as diagrams of relative light fall-off, distortion and longitudinal color aberration refer to film plane.







Longitudinal color aberration



Rodagon-G 480 mm f/8.4

